

snom[®] MeetingPoint

snom OCS_{edition}

klarVOICE
SUPERIOR AUDIO QUALITY

OmniSound[®]

CTI
inside



- **OmniSound[®] Full duplex wideband sound technology**
- **Management of up to 4 external participants**
- **Recording range up to 30 m² or 10 participants**
- **Simultaneous management of internal and external telephone listings (LDAP)**
- **Connection type for add-on microphones for a larger reception range**
- **Microsoft Office Communication Server 2007 R2 ready**
- **Multiple SIP registrations**
- **OpenVPN**

The first VoIP conference telephone from snom, the snom MeetingPoint, is the ideal addition for business travelers who must make frequent cross-location arrangements. With the snom MeetingPoint you are able to allow for a total of 4 external participants to attend at your conference from different locations all over the world - without expensive additional expenses for journeys or slow mail agreements. Control your travel budget and take care of the environment!

Of course the conference telephone, snom MeetingPoint, provides additional comfort, that you would expect

from snom: management of up to 4 external participants, LDAP, contact listings, possible snom Flexor CTI integration, excellent sound by OmniSound[®] 2.0 etc.

The snom MeetingPoint is perfectly qualified for use in middle to large conference rooms. As result of the reliable suppression of disturbing background noise and its excellent sound quality you can hold your telephone conferences in large groups of up to 10 persons without affecting the intelligibility of the call. Three speakers, equipped with full duplex wideband audio (7 kHz, codec "G.722") provide

balanced and full sound, which snom customers also know from the snom klarVOICE handset. The integrated special microphones ensure that your interlocutors feel as if you are sitting in the neighboring office - and not on the other side of the world!

The graceful styling of the snom MeetingPoint integrates ideally into each VoIP infrastructure and makes it a decent eye-catcher for your conference room.

TECHNICAL DATA **snom** MeetingPoint

GENERAL FEATURES

- **Size:** Diameter: 240 mm, Height: 77 mm
- **Display:** Background-lit graphical LCD, 128x64 pixels
- **Weight:** 1 kg
- **Color:** black
- **Keypad:** Alphanumeric 0-9, *, #, dial, hang up, mute, increase volume, menu, conference, recording, volume control, 5 keys for navigation in the menu system
- **Microphone:** circular (360°) recording characteristics
- **Reception range:** up to 30 m², < 10 persons
- **Speaker:** Frequency range: 150-15000 Hz playback
- **Volume:** 90 db SPL 0.5m. Equalizer function
- **Anti-theft protection:** Kensington security slot

CONNECTIONS

- **Network connection:** 1x RJ-45, PoE 10/100MBit
- **Power supply:** Power adapter 100-240 V AC/14 V DC - PoE
- **Add-on microphones:** modular 4/4 possible

SURROUNDING CONDITIONS

- **Temperature:** 5°–40° C.
- **Air humidity:** 20–80%
- **Suggested acoustic room conditions**
- **Reverberation time:** 0.5 S Rt 60
- **Background noise:** 45 dbA

PERMISSIONS

- **Telecom:** TBR21, 47 CFR part 68/TIA, IC CS-03 Issue 1999/01/01
- **EMC:** EN301 489-1,3. EN 300 220-1,2, FCC subpart B und C.
- **Electrical safety class:** UL 60950-1, EN 60950-1:200

snom technology AG

Charlottenstraße 68–71
10117 Berlin
tel/enum: +49 30 39833-0
fax: +49 30 39833-111
sip: info@snom.com
mail: info@snom.com